



800/70R32 and 680/85R32 VOLTYRE AGRO DF-5



Radial tubeless tires 800/70R32 DF-5 and 680/85R32 DF-5 under the brand VOLTYRE-AGRO are designed for operation on combines of Russian and foreign production, performing work in agriculture.

There tires may be installed on various modifications of combines. Tires have high load index and low pressure on the soil. Large, wide lugs protect the soil and plants. The tread pattern provides excellent traction and constant, uniform speed for harvesting. A high tread provides good traction, a safe, stable and comfortable ride due to a large contact area and a overlapping lugs in the middle of the tread.

The tires have self-cleaning properties due to the smooth area between the teeth of the tread. These tires make the machine more productive and contribute to lover fuel consumption.

The company JSC Voltyre=prom supplies thes 800/651.822. VOLTYRE ACRO DF=1 TL for the Glaas Russia.

Tire size	Load index and speed category	Max speed km\h	Load, kgf	Pressure, kPa	Overall diameter, mm	Max profile width, mm	Static loaded radius, mm	Rim contour designation (recommended/ approved)	Tread depth, mm	Weight, not more, kg
680/85R32	178A8	40	7500	240	1969	660	880	DW21B/ DW20B	50	310
800/70R32	175A8	40	6900	240	1945	785	870	DW27B/ DW25B, DH27B	50	400

TECHNICAL DATA

680/85R32	178A8	40	3525	4050	4650	5250	5850	6450	6975	7500	-	-
		30	3700	4300	4900	5600	6200	6900	7400	8000	-	-
		20	4300	4900	5700	6400	7100	7900	8500	9200	-	-
		10*	4500	5200	6000	6800	7600	8300	9000	9750	10500	-
		10**	5300	6100	7100	8000	8900	9800	10600	11400	12200	12750
800/70R32	175A8	40	3240	3720	4270	4830	5380	5930	6400	6900	-	-
		30	3470	3980	4570	5170	5750	6340	6850	7380	-	-
		20	3985	4575	5250	5940	6620	7290	7870	8490	-	-
		10*	4200	4835	5550	6280	6995	7710	8320	8970	9660	-
		10**	4955	5690	6530	7390	8230	9070	9800	10560	11245	11730
800/70R32	175A8	40 30 20 10*	3240 3470 3985 4200	3720 3980 4575 4835	4270 4570 5250 5550	4830 5170 5940 6280	5380 5750 6620 6995	5930 6340 7290 7710	6400 6850 7870 8320	6900 7380 8490 8970	- - - 9660	

Note: - Permissible limit deviations of inflation pressure values ± 10 kPa according to the manometer reading.

* -change of load is allowed for a short time not more than 10% of the working time.

** - for combine harvesters during operation with periodic load (except for combines operating on slopes with a slope of 11° - 22%).

For practical use in conditions of continuous operation at high values of torque, the values indicated in the line corresponding to a speed of 30 km/h are used.

JSC VOLTYRE-PROM

IS ONE OF THE LARGEST RUSSIAN MANUFACTURERS OF AGRICULTURAL AND INDUSTRIAL TIRES

MANUFACTURING RANGE:

- Agricultural, industrial and light truck tires

- Tubes and flaps

The products are produced under the brands VOLTYRE-AGRO, VOLTYRE-HEAVY, TITAN.

More than 100 sizes of tires are produced in accordance with the needs of the market.

Since 2016, the Company started producing the large-size agricultural tires (710/70R42, 800/65R32 etc.) and a wide range of industrial tires.

SCOPE OF WORK:

- Tires for operation on agricultural machinery of Russian and foreign production: combines, tractors, agricultural machinery and trailers;

- Tires for operation on construction machinery: hoisting-and-transport machines, excavators, graders, dump trucks, etc.

HEAD OF EXPORT MARKET GROUP DMITRY ILYUSHIN +7 8443 24 0499 E-MAIL: ILYUSHIN_DS@TITANCIS.RU CONTACTS

JSC VOLTYRE-PROM 7 AVTODOROGA, 25A, VOLZHSKY VOLGOGRAD REGION, 404103, RUSSIA

MADE

VOLTYRE PROM

WWW.VOLTYRE-PROM.RU WWW.TITAN-INTL.COM

EXPORT MANAGER ALEXEY MALICH +7 8443 24 0584 E-MAIL: MALICH_A0@TITANCIS.RU